

FT200

Mobile Cone Plant



Kodiak® Cone Crusher

- K200+ with high efficiency roller bearing design
- Variable-speed hydraulic drive
- Head diameter: 40 in (1,016 mm)
- Remote closed side setting (CSS) adjustment
 - Minimum CSS (application dependent):
3/8 in (9.5 mm)
 - Maximum CSS (application dependent):
2 in (50.8 mm)
- Interchangeable chamber configurations
 - Available concaves: coarse, medium, medium with feed slots, fine
- Field-replaceable base frame tub liners
- Field-replaceable V-Seat liners
- Patented liner retention assembly
 - Low-impact tramp iron relief (TIR) system
- Hydraulic cone brake
- Permanently precision-balanced with protected internal counterweights
- Feed hopper with level sensor
- 30 gallon (114 L) lube oil tank with Arctic Fox Hydraliner Heating System utilizing engine coolant to heat cone lube oil

Chassis

- High-strength, fabricated box-beam main frame
- 19.68 in (500 mm) wide tracks
- Maintenance platforms and access ladders
- Ground-level access for grease lubrication

Feed Hopper

- Wear-resistant, AR-lined loading area
- Hydraulic fold for transport
- Capacity: 7.5 cu. yds (5.7 cu. m)

Feed Conveyor

- Nominal 42 in (1,050 mm) wide belt
- EP630, 2-ply belt with vulcanized splice
- High-torque, variable-speed dual hydraulic motor drive
- Primary belt cleaner

Under Crusher Conveyor

- Nominal 42 in (1,050 mm) wide belt
- EP630, 2-ply belt with vulcanized splice
- Dual hydraulic motor drive
- Removable for maintenance
- Primary belt cleaner

Power & Hydraulics

- CAT C9.3B Tier 4F / Stage V, 456 hp (340 kW)
- 200 gallon (757 L) fuel tank
- Hydrostatic pump group
- 210 gallon (795 L) hydraulic tank with return filter
- 20 gpm (76 L/min) aux circuit for off-plant conveyor

Control System

- TRAC 10® control system with touchscreen
- Radio remote control with backup tether
- Crusher overload protection system (OPS)
- Automatic crusher feed regulation
- System fault tracking and storage

Dust Suppression System

- Manifold for customer filtered water supply
- Spray bars under crusher hopper, under-crusher conveyor head pulley and under-crusher conveyor mid-point
- Manifold-located ball valves for each spray bar


Optional Equipment

- Feed hopper bridge breaker
- Extended under crusher conveyor, 42 in (1,050 mm) wide, folds for transport
- Fixed, manual clean magnet with access platform and ladder
- Return conveyor, 24 in x 28 ft (600 mm x 13.4 m), fold for transport
- CAT C9.3B T3 diesel, 416 hp (310 kW)
- Engine enclosure filter kit
- Immersion heater for hydraulic tank
- Extreme cold weather lubrication
- Lighting package
- Security lock kit

Physical/Operating Characteristics

Dimension	Imperial	Metric
Base Unit Weight*	99,000 lb	44.9 t
Transport Width	9' 10"	3.0 m
Transport Length	56' 7"	17.3 m
Transport Height	11' 7"	3.5 m
Operating Width	9' 10"	3.0 m
with return conveyor	11' 9"	3.6 m
Operating Length	52' 2"	15.9 m
with extended under crusher conveyor	56' 11"	17.4 m
Operating Height	14' 11"	4.6 m
Feed Height	10' 6"	3.2 m
with extended under crusher conveyor	12' 6"	3.8 m

Operation



Transportation

