# GT104

## Mobile Screen Plant





#### **Vibrating Screen**

- 4 ft  $(1.22 \text{ m}) \times 9 \text{ ft } (2.74 \text{ m}) \text{ top and bottom deck}$
- 850 RPM adjustable amplitude
- Fixed 15-degree angle
- Top deck has side tensioned screen cloth, bottom deck has end tensioned screen cloth
- Modular top deck design

#### Hopper/Belt Feeder

- 5.25 cubic yard (4.01 cubic meter) heaped capacity
- Impact bed
- $13 \text{ ft } (3.96 \text{ m}) \times 42 \text{ in } (1,050 \text{ mm}) \text{ belt feeder}$
- Hydraulic variable speed single motor drive
- Toughflex grade X cover, vulcanized

#### **Overs Conveyor**

- Hydraulic variable speed drive
- Staggered impact bed
- Chevron belt, vulcanized
- 8 ft 10 in (2.69 m) fixed discharge height

#### **Under Screen Conveyor**

- 42 in under screen conveyor
- Grade II, 330 3-ply belting

#### **Bottom Deck Overs Conveyor**

- One (1) 25 ft (7.62 m)  $\times$  26 in (650 mm) fold out design
- Hydraulic variable speed
- 10 ft 5 in (3.18 m) fixed discharge height; 25-degree angle
- Chevron belt, vulcanized

#### **Fines Conveyor**

- One (1) 24 ft (7.32 m)  $\times$  26 in (650 mm) fold out design
- Hydraulic variable speed
- 11 ft (3.35 m) fixed discharge height
- Smooth belt, vulcanized, primary belt cleaner

#### Chassis

- Fabricated I-Beam frame
- Track mount design
- Pendant remote control

#### **Power Unit**

- Kohler 74hp Tier IV water cooled diesel engine
- 55 gal/208 L fuel tank
- Oil cooler
- 85 gal/322 L hydraulic oil reservoir
- Engine mounted hydraulic pumps to operate all plant functions
- NEMA-4 rated instrument panel
- Emergency stop

#### **Options**

- Punch plate top deck (flat or crowned)
- Grizzly bars top deck
- Tine deck top deck
- Wireless track remote
- Ball tray for bottom deck module
- Rear loader feed wings
- HD hydraulic grizzly for hopper
- Standard steel screen cloth both decks

### **Physical/Operating Characteristics**

Dimension	Imperial	Metric
Overall Length	35′ 1″	10.7 m
Operating Width	41′	12.5 m
Travel Length	35′ 1″	10.7 m
Travel Width	8'	2.4 m
Operating Height	11′ 8″	3.6 m
Feed Height (Front Feed)	8′ 7″	2.6 m
Travel Height	10′ 5″	3.2 m
Feed Height (Side Feed)	10′ 2″	3.1 m
Maximum Feed	12"	305 mm
Unit Weight	36,000 lb	16,329 kg

