

TTX SERIES

Rock Breaker System



Maximum Strength

Oversized hardened alloy pins, aluminum-bronze bushings, and thrust washers deliver maximum service under adverse conditions. Our induction-hardened chrome cylinder rods resist damage from fly rock. Four plate variable cross-section booms are specifically designed to minimize stress concentrations that typically lead to fatigue cracks

Longer Lifespan

Astec implements many design features that contribute to the overall life of the rock breaker. Clevis-type, high-pressure hydraulic cylinders equipped with high tensile steel-cast cylinder lugs provide maximum strength in rock breaking applications. The cylinder's self-aligning spherical ball bushings keep the equipment properly aligned and flexible during production hours throughout its lifespan

High Production

For high production applications, Astec combines enhanced motion control and boom position feedback for continuous speed giving the highest level of controllability while minimizing cycle times, improving operator fatigue and production

Pedestal Design

The turntable design offers a 330-degree full rotation with a hydraulic-driven slew-bearing drive producing a constant swing torque for consistent force during operation. All models are fitted with relief functions and back drive capability to absorb shock loading from the crusher without damaging the rock breaker system

Premium Controls

Astec offers a wide range of controls for all rock breaker systems. The breaker intel control system, Astec's premium controls, provide long-distance controls for single or multiple rock breaker operations, enhanced motion control and position feedback with collision avoidance, programmable ramp generation and flow sharing that easily integrate into your current plant. The system also provides monitoring and diagnostics. Our standard proportional control comes with your choice of game-style or joysticks control

Physical/Operating Characteristics

Model	Operating Weight Range*		Vertical Breaker Reach Forward**		Vertical Breaker Reach Down**		Maximum Reach Forward**		Recommended Breaker Range
	lb	kg	ft	m	ft	m	ft	m	
TTX30	44,570 - 49,420	20,215 - 22,410	30.83	9.1	26	7.9	40.58	12.3	BXR50 to BXR120
TTX36	48,450 - 53,300	21,975 - 24,170	35.33	10.8	33.33	10.1	45	12.3	
TTX40	49,700 - 53,300	22,543 - 24,188	38.75	14.2	35.25	10.7	46.75	14.2	BXR50 to BXR100
TTX45	52,145 - 54,445	23,653 - 24,696	43.91	14.4	42.5	12.68	53.75	16.3	BXR50 to BXR85
TTX48	53,700 - 56,000	24,358 - 25,401	47	14.3	44	13.3	54.83	16.7	

All specifications are subject to change without notice. All results may vary.

* Operating weight is dependent on final breaker size, power pack configuration and optional equipment

** Dimensions based referenced from center of swing rotation.

** Dimensions nominal (based on BXR65 breaker) and subject to change based on final breaker selection.